



GRAY EXHAUST HOSE



Application:

Clamped polyester fabric duct especially suitable:

- ◆ For extraction of high temperature air and cold air
- ◆ For solids such as dust, powder and fibers
- ◆ For gaseous media like vapors and smoke
- ◆ In dryer, automotive, aerospace, shipbuilding, military
- ◆ As bellows and compensator

Features:

- ◆ Good resistance to high temperature
- ◆ Good resistance to chemical substance
- ◆ Highly flexible and compressible
- ◆ External steel spiral protects against abrasion
- ◆ Firm clamping structure
- ◆ Small bending radius
- ◆ Kink-proof
- ◆ Light weight
- ◆ Flame-retardant

Material:

Wall: PVC coated polyester fabric

Clamp profile: Zinc plated steel slice







Working temperature range:

-20°C to +100°C

For more information, please contact: TechnoS Multiline LLC, Dubai, UAE

Tel: +971 (4)2237116 / 04-2223670 / 04-2237119 | Fax: +971 (4) 2279959 | Mobile: +971 (50) 6744049

Email: info@technos-me.com / tecmulti@eim.ae Website: www.technos-me.com

					
ID	Wall	Working Pressure	Vacuum Pressure	Bending Radius	Max. Length
mm	mm	bar	bar	Mm	m
51	0.32	0.85	0.350	76	10
63	0.32	0.68	0.290	94	10
76	0.32	0.60	0.250	114	10
82	0.32	0.55	0.200	123	10
102	0.32	0.50	0.150	153	10
127	0.32	0.40	0.100	190	10
152	0.32	0.30	0.060	228	10
159	0.32	0.25	0.050	238	10
178	0.32	0.20	0.040	267	10
203	0.32	0.15	0.030	304	10
228	0.32	0.12	0.025	342	10
254	0.32	0.10	0.020	381	10
279	0.32	0.08	0.018	418	10
305	0.32	0.07	0.012	457	10
356	0.32	0.06	0.010	534	10
381	0.32	0.05	0.010	571	10
406	0.32	0.05	0.010	609	10
457	0.32	0.04	0.010	685	10
482	0.32	0.04	0.010	723	10
508	0.32	0.04	0.010	762	10
533	0.32	0.03	0.008	799	10
558	0.32	0.03	0.006	837	10
584	0.32	0.03	0.006	876	10
610	0.32	0.02	0.005	915	10