



SS CORRUGATED HOSE










Hose: AISI 316L-DIN 1.4404-Z2CN17-12

Braid: AISI 304-DIN 1.4301-Z6CN18-09

Safety factor: 4:1

Temperature: -270 °C +700 °C

Tolerances: ± 0.2 mm: DN 6 ÷ DN 32, ± 0.3 mm: DN 40 ÷ DN 200

						
ID	OD Without Braid	OD With 1 Braid	Pressure	Dynamic	Static	Weight
mm	mm	mm	bar	mm	mm	Kg/m
6.1	9.6	10.6	100	100	25	0.140
10.0	14.3	15.4	90	150	40	0.190
12.2	16.7	17.8	80	200	50	0.210
16.2	21.6	22.8	70	200	50	0.410
20.3	26.8	28.0	64	200	70	0.480
25.4	32.2	33.7	50	200	90	0.650
34.3	41.1	43.0	40	250	110	0.760
40.0	49.8	52.5	30	250	130	1.050
50.2	65.0	67.2	28	350	175	1.440
65.4	80.8	83.0	24	410	200	1.689
79.9	95.0	97.0	18	450	205	2.084
100	116.7	119.0	16	560	230	3.749
125	149.0	152.5	12	660	280	4.930
150	174.9	177.5	10	815	320	5.837
198	225.0	228.0	8	1015	435	8.762

For more information, please contact: TechnoS Multiline LLC, Dubai, UAE

Tel: +971 (4)2237116 / 04-2223670 / 04-2237119 | Fax: +971 (4) 2279959 | Mobile: +971 (50) 6744049

Email: info@technos-me.com / tecmulti@eim.ae Website: www.technos-me.com