







## GRAY DUCT HOSE



				
Size	ID	OD	Bending Radius	Max. Length
mm	mm	mm	mm	m
22	21	28.60	35	30
25	25.4	31.10	45	30
30	31.8	38.64	50	30
40	38	45.00	55	30
50	50.8	57.20	65	30
60	60.5	68.50	75	30
75	76.5	83.54	95	30
100	101.2	108.94	125	30
125	127	135.20	140	15
140	140	148.5	150	15
150	152.4	161.10	205	15
160	160	170	210	15
200	204	214.40	270	10/15
250	253.0	264.00	370	10/15
300	305.0	319.00	470	10

Duct Hoses are highly specialized in performance. They are widely used for pneumatic transportation, dust collecting equipment, washing machines and air-conditioning equipments in buildings. Also suitable for carding machines and draw frames in textile machinery. This light weight, flexible, non-metallic hose has a specially compounded rigid PVC reinforcement which is helically wound and inseparably fused to the soft inner walls. By its unique construction, our ducting result in a thin, very smooth wall being almost completely protected from the crushing.

Temperature Range: 60 / 70°C

For more information, please contact: TechnoS Multiline LLC, Dubai, UAE

Tel: +971 (4)2237116 / 04-2223670 / 04-2237119 | Fax: +971 (4) 2279959 | Mobile: +971 (50) 6744049

Email: [info@technos-me.com](mailto:info@technos-me.com) / [tecmulti@eim.ae](mailto:tecmulti@eim.ae) Website: [www.technos-me.com](http://www.technos-me.com)