



4SP HOSE



Application:

Very high pressure Hydraulic Lines 165 to 450 bar and hydrostatic transmission lines. For use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Earthmoving & Material handling equipments and machineries/systems.

					
Dash size	ID	OD	Working Pressure	Burst Pressure	Bending Radius
	mm	mm	bar	bar	mm
-4	6.4	17.6	450	1800	150
-6	9.5	21.1	445	1780	180
-8	12.7	24.3	415	1660	230
-10	16	27.9	350	1400	250
-12	19	31.9	350	1400	300
-16	25.4	39.2	280	1120	340
-20	31.8	50.2	210	840	460
-24	38.1	56.6	185	740	560
-32	50.8	69.2	165	660	660

Applicable Standard:

Standard: EN 856-4SP.

Construction:

Core: Oil & water resistant Synthetic rubber.

Reinforcement: Four high tensile steel wire spirals.

Cover: Black Color, Synthetic rubber resistant to oil, weather and abrasion.

Temperature Range:

Continuous: -40°C to +100°C

Intermittent: max. 120°C

For more information, please contact: TechnoS Multiline LLC, Dubai, UAE

Tel: +971 (4)2237116 / 04-2223670 / 04-2237119 | Fax: +971 (4) 2279959 | Mobile: +971 (50) 6744049

Email: info@technos-me.com / tecmulti@eim.ae Website: www.technos-me.com