



## MH CLEAR PVC HOSE



### Description:

MH clear PVC tubing is manufactured from materials containing FDA approved ingredients and is suitable for food applications. MH tubing is resistant to a wide range of chemicals. Minimum frictional loss is achieved by the smooth bore.

### Applications:

MH tubing is extremely versatile and can be used in a wide range of low pressure applications including the transfer of liquids, acids & gases.

Construction: Clear unreinforced flexible PVC

### Special Features:

- Optimum flow is maintained by the smooth bore
- Tough, flexible and extremely durable under normal operating conditions
- Flexibility maintained even under cold weather conditions
- Nontoxic suitable for food use

Colours: Standard – Clear. Subject to minimum order quantity, colours & tints are available to order

Size range: **1/8" - 2"**







Standard Length: 30 meters supplied in a coil. Subject to minimum order quantity, longer or shorter lengths are available to order.

Temperature Range: -15°C to +65°C

For more information, please contact: Technos Multiline LLC, Dubai, UAE

Tel: +971 (4)2237116 / 04-2223670 / 04-2237119 | Fax: +971 (4) 2279959 | Mobile: +971 (50) 6744049

Email: [info@technos-me.com](mailto:info@technos-me.com) / [tecmulti@eim.ae](mailto:tecmulti@eim.ae) Website: [www.technos-me.com](http://www.technos-me.com)

					
ID	OD	Wall	Bending Radius	Weight	Max. Length
mm	mm	mm	mm	Kg/coil	m
3.0	6.0	1.5	24	0.78	30
4.0	6.0	1.0	32	0.58	30
4.0	10.0	3.0	32	2.43	30
5.0	8.0	1.5	40	1.13	30
6.0	9.0	1.5	48	1.31	30
6.0	12.0	3.0	48	3.12	30
8.0	11.0	1.5	64	1.65	30
8.0	14.0	3.0	64	3.83	30
9.0	12.0	1.5	72	1.83	30
10.0	13.0	1.5	80	2.00	30
10.0	16.0	3.0	80	4.52	30
12.0	15.0	1.5	96	2.35	30
12.0	16.0	2.0	96	3.25	30
12.0	18.0	3.0	96	5.22	30
13.0	19.0	3.0	104	5.57	30
16.0	22.0	3.0	128	6.61	30
19.0	22.0	1.5	152	3.56	30
19.0	25.0	3.0	152	7.65	30
22.0	28.0	3.0	176	8.69	30
25.0	31.0	3.0	200	9.74	30
32.0	38.0	3.0	256	12.17	30
32.0	41.0	4.5	256	19.04	30
38.0	47.0	4.5	304	22.17	30
45.0	54.0	4.5	360	25.82	30
50.0	62.0	6.0	400	38.95	30