









## R6 HOSE



### Application:

Very low pressure and low impulse hydraulic lines 20 to 35 bar.  
for use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Agricultural, Stationary equipments and hydraulic systems.

						
Dash size	ID	ID	OD	Working Pressure	Burst Pressure	Bending Radius
	inch	mm	mm	bar	bar	mm
-4	1/4	6.3	13	28	112	65
-5	5/16	8.2	14.5	28	112	80
-6	3/8	9.8	16.5	28	112	80
-8	1/2	12.9	20	28	112	100
-10	5/8	16.2	23	24	96	125
-12	3/4	19.2	26.5	21	83	150
-14	1	25.3	33	20	80	170

### Applicable Standard:

Standard: SAE J517 – 100 R6 / EN 854.

### Construction:

Core: Oil resistant Synthetic rubber.

Reinforcement: Single fiber braid.

Cover: Black Color, Synthetic rubber resistant to oil, weather and abrasion.

### Temperature Range:

Continuous: -40°C to +120°C

For more information, please contact: TechnoS Multiline LLC, Dubai, UAE

Tel: +971 (4)2237116 / 04-2223670 / 04-2237119 | Fax: +971 (4) 2279959 | Mobile: +971 (50) 6744049

Email: info@technos-me.com / tecmulti@eim.ae Website: www.technos-me.com