



RED DUCT HOSE



Application:

Suction hose, especially suitable:

- ◆ For transmission hot air, chemical fumes and industrial fumes
- ◆ For printing machines, blowers
- ◆ For exhausting gas, engine construction, engine warming, aircraft construction and military construction

Features:

- ◆ Double-layer of silicone coated glass fiber fabric
- ◆ Extremely good heat resistance
- ◆ Leak-proof
- ◆ Smooth interior
- ◆ Highly flexible
- ◆ Small bending radius
- ◆ Kink-proof

Material:

Wall: Silicone coated glass fiber fabric

Spiral: Spring steel wire

Reinforcement: Glass fiber cord

Delivery Variants: Wireless sleeves

Working Temperature Range:








-70°C to +260°C

Short time to +280°C

For more information, please contact: Technos Multiline LLC, Dubai, UAE

Tel: +971 (4)2237116 / 04-2223670 / 04-2237119 | Fax: +971 (4) 2279959 | Mobile: +971 (50) 6744049

Email: info@technos-me.com / tecmulti@eim.ae Website: www.technos-me.com

						
ID	OD	Wall	Working Pressure	Burst Pressure	Bending Radius	Max. Length
mm	mm	mm	bar	bar	mm	m
25	29	0.4	2.7	0.70	43	4
32	36	0.4	2.7	0.64	54	4
38	43	0.4	2.6	0.60	64	4
51	56	0.4	2.5	0.51	84	4
63	68	0.4	2.3	0.46	102	4
76	81	0.4	2.1	0.42	121	4
83	88	0.4	2.0	0.40	132	4
89	94	0.4	2.0	0.38	141	4
102	107	0.4	1.9	0.35	160	4
114	120	0.4	1.6	0.29	180	4
127	133	0.4	1.5	0.26	199	4
152	158	0.4	1.3	0.18	237	4
165	172	0.4	1.2	0.15	258	4
178	184	0.4	1.0	0.13	276	4
203	209	0.4	0.8	0.10	313	4
254	260	0.4	0.6	0.08	390	4
305	311	0.4	0.5	0.07	466	4